

# Outline Wallgrazer 120 | 28W

## Product Reference

Environment Outdoor

Installation Ceiling Surface

## Construction & Materials

Housing Extruded Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish Anodised Aluminium

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 23.1W


System Power Watts 26.6W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. >0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 34-36Vdc/700mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Outline Wallgrazer 120</b>	<b>28W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>91°x30°</b>	<b>AL</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL		
<b>Outline Wallgrazer 120</b>	<b>28W</b>	2846	107	2700K	<b>WW27K</b>	<b>91°x30°</b>	Anodised Aluminium	<b>AL</b>	Non Dimmable	<b>On/Off</b>
		2926	110	3000K	<b>WW30K</b>			CRI90	Phase Dimmable	<b>PDIM</b>
		3086	116	4000K	<b>NW40K</b>			Dali Dimmable	<b>DDIM</b>	
		3139	118	5700K	<b>CW57K</b>			Bluetooth Dimmable	<b>BTTM</b>	
				2700K-5700K	<b>TW</b>			Casambi	<b>CBTM</b>	
<b>Outline Wallgrazer 120</b>	<b>28W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>91°x30°</b>	<b>AL</b>	<b>On/Off</b>		

Abby reserves the right to discontinue any product from its collection at any time whatsoever and without prior notice

[www.abbylighting.com](http://www.abbylighting.com)