

Circulo S 60 | 34W

Product Reference

Environment Indoor

Installation Ceiling Surface

Construction & Materials

Housing Extruded and Sheet Aluminium

Primary Lens -

Primary Reflector White Optics

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Opal PC, Microprismatic

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 29.1W


System Power Watts 33.4W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 43V-48Vdc/700mA

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable

Ordering Details

| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|---------------------|------------|--------------|--------------|------------|------------|---------------|
| | Circulo S 60 | 34W | WW27K | CRI80 | 95° | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | CRI | ANGLE | FINISH | CONTROL | |
|---------------------|------------|-------|----------|--------------|--------------|------------|------------|-------------------------|--------------------------|
| Circulo S 60 | 34W | 4175 | 125 | 2700K | WW27K | 95° | White | SWH Non Dimmable | |
| | | 4242 | 127 | 3000K | WW30K | | CRI90 | Black | SBL Dali Dimmable |
| | | 4342 | 130 | 4000K | NW40K | | Custom | CSM Casambi | CBTM |
| | | 4409 | 132 | 5700K | CW57K | | | | |
| | | | | 2700K-5700K | TW | | | | |
| Circulo S 60 | 34W | | | WW27K | CRI80 | 95° | SWH | on/Off | |

